



# **Choice of Materials for Events and Exhibitions at the University of Zurich**

## Guidelines for Organisers and Exhibitors

Publisher University of Zurich, Directorate for Real Estate and  
Facility Management, Safety, Security and Environment

Source <https://www.ib.uzh.ch/de.html>

Version 23-01, 12<sup>th</sup> of September 2023

## Revision History

<b>Date</b>	<b>Version</b>	<b>Chapters</b>	<b>Remark</b>
14.09.2020	20-01	all	Enactment of the document by Fire Prevention and Emergency Organisation
16.02.2022	22-01	all	Additions in chapter 3, revision of the glossary
12.07.2022	22-02	3 and 4	Correction of norm
16.08.2022	22-03	5	Additional contact information
12.09.2023	23-01	2.1 and 5	Deletion Forex RF2 and adjustment contact details

# Contents

<b>1 General</b>	<b>4</b>
1.1 Scope	4
1.2 Deviations	4
1.3 Legal Basis	4
<b>2 (Building) Materials</b>	<b>5</b>
2.1 Permissible (Building) Materials	5
2.2 Prohibited (Building) Materials	7
2.3 Usage of electronic devices	9
2.3.1 Norms	9
<b>3 Certifications</b>	<b>9</b>
<b>4 Glossary</b>	<b>10</b>
<b>5 Contact Information</b>	<b>10</b>

# 1 General

Disclaimer: This is a translation of the original document in German. It is provided for information purposes only and has no legal bearing.

## 1.1 Scope

These guidelines define which types of materials are allowed for usage at events and exhibitions at the University of Zurich. They are binding for both internal and external organisers.

Those who are responsible for the organisation of the events are required to send a full bill of materials to the host. Any questions and possible problems are to be discussed with the Fire Safety Officer of the University of Zurich. See chapter 5 for contact information.

## 1.2 Deviations

Should any circumstances arise which necessitate a deviation from these guidelines when organising an event, it is required to get permission from the Fire Safety Officer beforehand. See chapter 5 for contact information.

## 1.3 Legal Basis

These UZH guidelines are based on the fire prevention norms by the VKF<sup>1</sup>. Those are legally binding and to be followed.

<sup>1</sup> VKF: Vereinigung Kantonaler Feuerversicherungen (Association of Cantonal Fire Insurances)

## 2 (Building) Materials

The list of materials below is neither complete nor final. Should any materials be used, which are not listed below, it is required to contact the UZH Fire Safety Officer beforehand. See contact information in chapter 5.

In both vertical and horizontal escape routes<sup>2</sup> only materials of the fire behaviour group RF1 are allowed. In buildings of special, open construction (for example KOL and Y24) materials of the group RF2 can be used under the condition that its usage is discussed with the Fire Safety Officer of the University of Zurich prior to the event.

The usage of materials belonging to all other groups is exclusively allowed within rooms.

### 2.1 Permissible (Building) Materials

Permissible (building) materials for events and exhibitions (only RF1 in escape routes)	Item or description of material	Technical Requirements	Fire behaviour group
	Aluminium and aluminium alloys	-	RF1
	Concrete, concrete additives, gas concrete, lead, iron, steel, stainless steel, fibrous cement	-	RF1
	Gypsum and gypsum-based plaster	-	RF1
	Glass, ceramic glass, foam glass	-	RF1
	Quicklime, calcium silicate, ceramics	-	RF1
	Mineral additives, mineral wool, mortar with inorganic binding agents	-	RF1
	Natural stones, clay, cement	-	RF1
	Terrazzo	-	RF1
	Vermiculite	-	RF1
	Zinc and zinc alloys	Non-dispersed	RF1
Copper and copper alloys	Non-dispersed	RF1	

<sup>2</sup> Stairwells are considered vertical escape routes and corridors are considered horizontal escape routes.

Item or description of material	Technical Requirements	Fire behaviour group
Plasterboard / SN EN 520  Paper / SN EN ISO 536	Density $\geq 800$ kg/m <sup>3</sup> Thickness $\geq 6,5$ mm  Paper weight $\leq 220$ g/m <sup>2</sup> ( $\leq 5\%$ inorganic additives)	<b>RF1</b>
Cement-bonded particle board	Density $\geq 1200$ kg/m <sup>3</sup> Thickness $\geq 10$ mm Content of cement $\geq 75\%$ by mass	<b>RF1</b>
Phenolic and formaldehyde resins	-	<b>RF2</b>
PTFE ("Teflon")	-	<b>RF2</b>
Decorations, blinds, and tablecloths	-	<b>RF2</b>
Deciduous trees	Oak, robinia, afrormosia, afzelia, bilinga, iroko, makore, teak, meranti, sapele, sipo, wenge	<b>RF2</b>
Parquet and wood flooring	Sealed or oiled parquet, maple, beech, oak, ash	<b>RF2</b>
	Wood flooring made of RF2 material	<b>RF2</b>
Particle board	Only if certified RF2	<b>RF2</b>

## 2.2 Prohibited (Building) Materials

	Item or description of material	Technical Requirements	Fire behaviour group
Impermissible (building) materials for events and exhibitions outside of closed rooms	Deciduous trees	Maple, beech, alder, ash, cherry, walnut	<b>RF3</b>
	Coniferous trees	Spruce, fir, larch, red cedar, cedar, arolla pine	<b>RF3</b>
	Wood fibreboard	MDF, hard and porous fibreboard Density $\geq 230$ kg/m <sup>3</sup>	<b>RF3</b>
	Solid wood panels	Solid wood panels, cross-laminated timber plates	<b>RF3</b>
	OSB		<b>RF3</b>
	Plywood	Plywood panels	<b>RF3</b>
	CV-Floorings / SN EN 653	Minimum weight = 1000 g/m <sup>2</sup> Maximum weight = 2800 g/m <sup>2</sup> Minimum thickness = 1,1 mm	<b>RF3 (cr)</b>
	Parquet and wood flooring	Wood floorings made of RF3 material	<b>RF3</b>
	Elastomer floorings with smooth surface / SN EN 1817	Minimum weight = 3000 g/m <sup>2</sup> Maximum weight = 6000 g/m <sup>2</sup> Minimum thickness = 1,8 mm	<b>RF3 (cr)</b>
	Elastomer floorings with smooth surface and foam backing / SN EN 1816	Minimum weight = 3400 g/m <sup>2</sup> Maximum weight = 4300 g/m <sup>2</sup> Minimum thickness = 4 mm	<b>RF3 (cr)</b>
	Elastomer floorings with moulded surface / SN EN 12199	Minimum weight = 4600 g/m <sup>2</sup> Maximum weight = 6700 g/m <sup>2</sup> Minimum thickness = 2,5 mm	<b>RF3 (cr)</b>
	PVC tiles of medium elasticity / SN EN 654	Minimum weight = 4200 g/m <sup>2</sup> Maximum weight = 5000 g/m <sup>2</sup> Minimum thickness = 2 mm	<b>RF3 (cr)</b>
	Linoleum on cork backing / SN EN 687	Minimum weight = 2900 g/m <sup>2</sup> Maximum weight = 5300 g/m <sup>2</sup> Minimum thickness = 2,5 mm	<b>RF3 (cr)</b>

Impermissible (building) materials for events and exhibitions outside of closed rooms	Item or description of material	Technical Requirements	Fire behaviour group
	Linoleum flooring / SN EN 548	Minimum weight = 2300 g/m <sup>2</sup> Maximum weight = 4900g/m <sup>2</sup> Minimum thickness = 2 mm	RF3 (cr)
	Silicone elastomer		RF3 (cr)
	PVC floorings with backings based on cork / SN EN 652	Minimum weight = 3400 g/m <sup>2</sup> Maximum weight = 3700 g/m <sup>2</sup> Minimum thickness = 3,2 mm	RF3 (cr)
	PVC flooring with foam backing / SN EN 651	Minimum weight = 1700 g/m <sup>2</sup> Maximum weight = 5400 g/m <sup>2</sup> Minimum thickness = 2 mm	RF3 (cr)
	Wood-based panels (density ≥ 580 kg/m <sup>3</sup> )	-	RF3
	Polypropylene (PP)	-	RF3 (cr)
	Cellulose-Acetate (CA)	-	RF3
	Epoxy resin (EP)	-	RF3 (cr)
	Polymethylmethacrylate (PMMA)	-	RF3
	Polychloroprene (neoprene)	-	RF3 (cr)
	Fibreglass	-	RF3 (cr)
	Polystyrene (PS)	-	RF3 (cr)
	Soft polyvinylchloride	-	RF3 (cr)
	Polyvinylchloride, flexible polyurethane foam	-	RF3 (cr)
	Polyethylene (PE)	-	RF3
	Hard polyvinylchloride	-	RF2 (cr)
Polyvinylidene chloride (PVDC)	-	RF2 (cr)	



### **2.3 Usage of electronic devices**

The mounting of video systems, monitors and similar devices in escape routes is only allowed, if the required minimum width of the escape route can be guaranteed at all times and if the device is manufactured in accordance with one of the following norms:

#### **2.3.1 Norms**

1. SN EN 62368-1:2014 Audio/video, information and communication technology equipment Part 1. Safety requirements
2. SN EN 60950-1+A11+A1+A12+A2-AC:2011 Information technology equipment - Safety - Part 1: General requirements
3. SN EN 60065+A1+A11+A2+A12:2011 Audio, video and similar electronic apparatus. Safety requirements

## **3 Certifications**

Each inquiry towards Fire Prevention and Emergency Organisation concerning events and exhibitions at the University of Zurich needs to include the certifications of the used materials and items.

Important!

Only certifications issued in accordance with the VKF or with SN EN 13501-1:2009 can be accepted and approved.

Other certifications like B1 or B2 cannot be accepted.

When requesting the certificates from the exhibitors and manufacturers it is necessary to verify the validity of the certificate. Notably certificates whose validity expired, cannot be accepted.

The relevant authority which issued the permit for the space, is responsible for informing the organisers and exhibitors about these guidelines.

## 4 Glossary

Fire behaviour group	Classification according to VKF fire index	Classification according to SN EN 13501-1:2009	Fire behaviour
<b>RF1</b>	6.3 / 6q.3	<b>A1</b> A2-s1,d0	No contribution to fire / virtually not flammable
<b>RF2</b> RF2 (cr) «Critical»	5 (200°C).3 / 5.3 / 5 (200°C).2 / 5.2 / <b>Critical behaviour</b> 5(200 °C).1 / 5.1	A2-s1,d1 - C-s2,d1	Little contribution to fire
<b>RF3</b> RF3 (cr) «Critical»	4.3 / 4.2 <b>Critical behaviour</b> 4.1	D-s1,d0 - D-s2,d1	Acceptable contribution to fire
<b>RF 4</b>	3.3 3.2 <b>Critical behaviour</b> 3.1	-	Unacceptable contribution to fire
<b>Not a building material</b>	2.3 / 2.2 / 2.1 / 1.3 / 1.2 / 1.1	<b>F</b>	Not a building material

<b>Critical Behaviour</b>	Smoke emission according to VKF fire index	Fire behaviour
s1	3	Little to no smoke emission
s2	2	Limited smoke emission
s3	1	Unlimited smoke emission
d0	-	No burning droplets or particles falling off
d1	-	Limited burning droplets or particles falling off
d2	-	A lot of burning droplets or particles falling off

## 5 Contact Information

Feel free to contact [brandschutz@su.uzh.ch](mailto:brandschutz@su.uzh.ch) for any questions about fire prevention at events, especially for questions about the choice of materials.

For general questions about fire prevention contact:

University of Zurich  
 Safety, Security and Environment  
 Winterthurerstrasse 190  
 8057 Zürich  
[www.su.uzh.ch](http://www.su.uzh.ch)

**Cem Yildiz**  
 Fire Safety Officer  
 +41 44 635 55 00  
[cem.yildiz@uzh.ch](mailto:cem.yildiz@uzh.ch)